

FONDA 900

OPERA

General data

Dimensions (width x depth x height)	900 x 580 x 80 mm
Cooking technology	Induction
Number of cooking zones	4
Cooking surface material	KeraBlack+ glassceramic
Aspiration unit	Floor brushless blower

Induction cooking data

Multiphase supply voltage	380 – 415 V 2N
Single-phase supply voltage	220 – 240 V 1N
Frequency	50/60 Hz
Two phase power supply/fuse protection	2 x 16 A
Single phase power supply/fuse protection	1 x 32 A
Maximum power consumption	7,4 kW
Cooktop power levels	1 – 9, Power – slider control
Cooking zones size	220 x 184 mm
Cooking zone power output	2,1 kW (3,7 kW- Booster)
Bridge zone power output	3,7 kW
Power limitation	1,0 - 1,5 - 2,8 - 3,7 - 4,5 - 6,0 kW

Aspiration datas

Single-phase supply voltage	220 – 240 V, equipped with schuko plug
Frequency	50/60 Hz
Maximum power consumption	169 W
Maximum engine power	850 m ³ /h
Db(A)	68
Aspiration power levels	1 – 3, Power
Aspiration mode	External (A), not included Internal (B) Recirculation (C)
Air ducting system	222 x 90 mm

